



MINI-RAD F30 HD M

HIGH RADIATION TOLERANT MINI HD CAMERA WITH MOTORIZED FOCUS AND MIRROR

MINI-RAD F30 HD M is a compact high radiation tolerant color camera with motorized focus. The mirror attachment enables inspection inside tubes and other narrow spaces.

APPLICATIONS

- Suitable for placement on an actuator or tool where it is used for inspection and monitoring in confined spaces
- Controlled by CCU50 which controls camera on/off, focus and manual adjustments of the lights

BENEFITS

- Small size
- Very radiation tolerant
- Motorized focus
- The lights beside the mirror can operate underwater as well as in air
- 2 channels for individual LED light control

SPECIFICATIONS

Diameter	30 mm (1,18")
Length	166 mm (6,5")
Weight	400 g (0,9 lbs)
Housing material	Stainless steel
Radiation tolerance (dose rate)	1 000 Gy/h (100 000 rad/h)
Radiation tolerance (total dose)	50 000 Gy (5 000 000 rad)
Resolution HD version	720p
Maximum temperature	50°C, 122°F
Water tightness	min 3,5 bar, 50 psi

CALCULATED VALUES FOR DIFFERENT LENS OPTIONS

Focal length	4,0 mm
Field of view in air	H52° x V31°
Field of view in water	H39° x V23°
Focal length	6,0 mm
Field of view in air	H34° x V21°
Field of view in air	H26° x V16°
Focal length	8,0 mm
Field of view in water	H26° x V16°
Field of view in water	H20° x V12°

We reserve the right to alter specifications without prior notice

Focal length, non-browning lens	5,0 mm
Field of view in air	H41° x V25°
Field of view in water	H30° x V18°

We reserve the right to alter specifications without prior notice

MINI-RAD F30 HD M IMAGES



We reserve the right to alter specifications without prior notice